

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) A system for holding and mixing a first container of paint having a first volume and a second container of paint having a second volume less than the first volume, the system comprising:
 - a holder comprising a clamp having a plate configured to apply pressure to the first container;
 - a motor configured to move the holder about at least one axis; and
 - a platform configured for being removably placed within the holder and configured to support the second container from below the second container, wherein the plate applies pressure to the first and second container during a single mixing operation.
2. (Original) The system of claim 1, wherein the holder is balanced for both the first container and the second container supported by the platform placed in the holder.
3. (Original) The system of claim 1, wherein the platform is configured to support at least four second containers.
4. (Original) The system of claim 1, wherein the platform includes a stop proximate an edge of the platform.
5. (Currently Amended) The system of claim 1, wherein the platform is composed of a material selected from a group ~~including~~ consisting of a metal, a polyester resin, and a resilient material.
6. (Original) The system of claim 1, wherein the perimeter of the platform is less than the perimeter of the holder.
7. (Original) The system of claim 1, wherein the first container volume is one gallon (4 liters) and the second container volume is one quart (1 liter).

8.-13. (Cancelled).

14. (Currently Amended) An apparatus for holding and mixing a first container of paint having a first volume and a second container of paint having a second volume less than the first volume, the apparatus comprising:

a means for holding comprising a means for clamping to apply pressure to the first container;

a means for moving configured to move the means for holding about at least one axis; and

a means for adjusting height configured for being removably placed within the means for holding and configured to support the second container from below the second container, wherein the means for clamping applies pressure to the first and second container during a single mixing operation.

15. (Original) The apparatus of claim 14, wherein the means for holding is balanced for both the first container and the second container supported by the means for adjusting height placed in the means for holding.

16. (Original) The apparatus of claim 14, wherein the means for adjusting height can support at least four second containers.

17. (Original) The apparatus of claim 14, wherein the means for adjusting height includes a means for stopping.

18. (Original) The apparatus of claim 14, wherein the perimeter of the means for adjusting height is less than the perimeter of the means for holding.

19. (Original) The apparatus of claim 14, wherein the first container volume is one gallon (4 liters) and the second container volume is one quart (1 liter).

20. (New) An apparatus for holding and mixing a first container of paint and a different size second container of paint, the apparatus comprising:

a holder comprising a clamp having a plate configured to apply pressure to the containers;

a motor configured to move the holder about at least one axis; and

a platform configured for removable placement within the holder below the second container, wherein the second container is positioned to allow the plate to apply pressure to both containers during a single mixing operation.

21. (New) The system of claim 20, wherein the platform is configured to support at least four second containers.

22. (New) The system of claim 20, wherein the platform includes a stop proximate an edge of the platform.

23. (New) The system of claim 20, wherein the platform is composed of a material selected from a group consisting of a metal, a polyester resin, and a resilient material.

24. (New) The system of claim 20, wherein the perimeter of the platform is less than the perimeter of the holder.

25. (New) The system of claim 20, wherein the first container volume is one gallon (4 liters) and the second container volume is one quart (1 liter).